



Ancillary, Hospitality, Residential, Retail







Downlights

Architectural




## **OCTO Prism Pro Anti-Glare**

OCTO Prism Pro Anti-Glare FRD Connected by WiZ Code: APRIPAG/1/OCTOW/RGBTW







Category

**Application** 

Specification



## PRODUCT FEATURES

- IP65 Dimmable LED WiZ enabled tunable white Fire Rated
- Tunable between 2700K 6500K via WiZ app and voice control
- Anti-glare design to create visual comfort
- Remote driver with 2x1.5mm² + CPC loop-in, loop-out colour coded push fit piano terminals provide an easy and efficient installation
- Connects directly to your WiFi network using Bluetooth technology to support seamless pairing Anti-Glare Downlight suitable for residential and commercial applications
- Supplied with matt white bezel as standard.
- New innovative 2 part detachable connector design allows initial wiring and testing to be completed first, then simply plug the downlight back to the connector, ensuring a quick and simple installation
- Low profile design and remote driver allow installation into shallow ceiling voids

GENERAL INFORMATION		
Wattage	8W	
Lumens Delivered	380lm - 430lm (2700K - 6500K)	
Lm/W	57lm/W	
Beam Angle	55	
CRI	80	
CCT	2700-6500K	
Input	220/240V	
Operating Temp	-20°C - 35°C	
SDCM	6	
UGR	17	
Cut-Out Size	73mm	

TECHNICAL INFORMATION		
Light Source	LED	
Colour / Finish	White	
Fire Rated	Yes	
IP Rating	IP65	
Class Protection	2	
Internal / External	Internal	
Surface / Recessed / Suspended	Recessed	
Lumen Depreciation L70 B50	L70 B50 54,000h	
Warranty (Years)	5	
CE Mark	Yes	
Diameter	88 mm	
Height	80 mm	

www.ansell-lighting.com Warrington: +44 (0) 1942 433333 Belfast: +44 (0) 2890 773750

