

# Ei413



## RadioLINK Panel Interface Module



- Links Aico alarms to a Panel System
- 12-24V DC powered - from the panel system
- RadioLINK Wireless interconnection
- 5 year guarantee



### Description

The Ei413 RadioLINK Panel Interface Module provides an interface between RadioLINK alarms and fire alarm/security alarm panels. The module will receive 'Fire', 'CO' and 'Service' signals from RadioLINK devices and switch the relevant built-in relay

### Technical

<b>RF Frequency (MHz)</b>	868.499	<b>RF Range (m)</b>	>100 in free air
<b>Indicators</b>	Blue - RF transmission	<b>Power Consumption (W)</b>	0.2
<b>Technologies</b>	RadioLINK		

### Dimensions & Weights

<b>Depth (mm)</b>	52	<b>Height (mm)</b>	91
<b>Width (mm)</b>	91	<b>Product weight (kg)</b>	0.156
<b>Packaged weight (kg)</b>	0.176		

### Approvals & Warranty

<b>Certification/Approvals</b>	EN 300 220-1 / EN 300 220-2 / EN 301 489-1 / EN 301 489-3	<b>Warranty</b>	5 year warranty
<b>EAN Number</b>	5099383004748		

### Environmental

<b>Humidity Range (%)</b>	15-95	<b>Temperature Range (°C)</b>	-10 to 40
---------------------------	-------	-------------------------------	-----------