



ATLEVO5

Topline EVO CCT Multi Wattage 1500mm



Features

High performance, multi-wattage LED CCT batten suitable for industrial and multi-purpose applications

Selectable CCT between 3000K, 4000K and 5700K

High efficiency up to 140 lm/W

Power selectable; offering high and low output option in each length

Excellent light uniformity through high transmittance polycarbonate diffuser

Instant light output with unlimited switching

Innovative spring clip gear tray release aids fast and easy installation

Self-test, lithium emergency as standard

Dimmable and Smart options available

Powered by Tridonic

General Information

Lamp Type	LED
Colour / Finish	White
IP Rating	IP20
IK Rating	IK06
Class Protection	1
Internal / External	Internal
Surface / Recessed / Suspended	Surface,Suspended
Lifetime (Hrs)	L70 54,000h
Warranty (Years)	5
Length (mm)	1,525 mm
Width (mm)	70 mm
Height (mm)	60 mm

Technical Information

Wattage	24/43W
Lumens Delivered	3300/6000lm (4000K)
Lm/W	140lm/W
Beam Angle	105/140
CRI	80
CCT	3000/4000/5700K
Input	220/240V
Hertz	50/60Hz
Operating Temp	-10°C to 40°C
SDCM	6
UGR	25

Datasheet generated from <https://onetimepim.com> last updated Tuesday, July 26, 2022 10:08:35 PM

