



ATORPLED2X4

Tornado PRO Twin 1200mm



Features

Robust non-corrosive batten ideal for industrial applications and ancillary areas

Ultra slim IP65 LED NCF linear

High efficiency up to 161 Lm/W

Unique base design caters for multiple installation methods

Installer friendly embedded features aid accurate and fast installation for any application

Quick release LED array / gear tray assembly provides the installer the means to faster installation / maintenance

Fast latching / permanently located stainless steel side clips ensure a quick and secure connection

Self-test emergency as standard with Li-ion battery technology, reducing charge time and running costs

Powered by Tridonic

General Information

Lamp Type	LED
Colour / Finish	Grey
Bluetooth Enabled	Yes
IP Rating	IP65
IK Rating	IK07
Class Protection	1
Internal / External	Internal / External
Surface / Recessed / Suspended	Surface,Suspended
Lifetime (Hrs)	L80 B10 54,000h
Warranty (Years)	7
CE Mark	Yes
Length (mm)	1,265 mm
Width (mm)	115 mm
Height (mm)	70 mm
Accessories	ATORPLED/SSKIT/SINGLE, ATORPLED/SSKIT/TWIN

Technical Information

Wattage	41W
Lumens Delivered	4500lm
Lm/W	109lm/W
Beam Angle	100/120
CRI	80
CCT	4000K
Input	220/240V
Hertz	50/60Hz
Operating Temp	-10°C to 40°C
SDCM	6

Datasheet generated from <https://onetimepim.com> last updated Thursday, October 6, 2022 8:27:12 AM



