


# KOMFORT EC LB

## Heat recovery air handling units

### Features

- Air handling units for efficient supply and exhaust ventilation in flats, houses, cottages and other buildings.
- Used to create controlled energy-saving ventilation systems.
- The heat recovery technology is used to minimize ventilation heat losses.
- Control of air exchange for creating comfortable indoor microclimate.
- Compatible with round Ø 160, 200 or 250 mm air ducts.




### Design

- The casing is made of double-skinned aluzinc panels, internally filled with mineral wool layer 40 mm for heat- and sound-insulation.
- The casing has mounting brackets with anti-vibration rubber mounts for easy installation.
- The unit is equipped with service hatches on the side panels for easy maintenance of filters. This design enables the left-hand and right-hand installation of the unit.
- The spigots are located at the sides of the unit and are equipped with rubber seals for airtight connection to the air ducts.

### Fans

- High-efficient external rotor EC motors and centrifugal impellers are used for air supply and exhaust.
- The forward curved blades in **KOMFORT EC LB(E)300/LB(E)400** provide permanent air flow.
- The **KOMFORT EC LB(E)700** model has impellers with backward curved blades.
- EC motors have the best power consumption to air capacity ratio and meet the latest demands concerning energy saving and high-efficient ventilation.
- EC motors are featured with high performance, low noise level and totally controllable speed range.
- The impellers are dynamically balanced.



## Heat recovery

- The **KOMFORT EC LB(E)...** unit is equipped with a plate counter-flow polystyrene heat exchanger for heat recovery. In the unit condensate is collected and drained to the drain pan under the heat exchanger.



- The **KOMFORT EC LB(E)...-E** unit is equipped with an enthalpy plate counter-flow heat exchanger for energy (heat and humidity) recovery. Due to humidity recovery condensate is not generated in the enthalpy heat exchanger.



- The air flows are completely separated in the heat exchanger. Thus smells and contaminants are not transferred from the extract air to the supply air.
- Heat recovery is based on heat and/or humidity transfer through the heat exchanger plates. In the cold season supply air is heated in the heat exchanger by transferring the heat energy of warm and humid extract air to the cold fresh air. Heat recovery minimizes ventilation heat losses and heating costs respectively.
- In the warm season the heat exchanger performs reverse and intake air is cooled in the heat exchanger by the cool extract air. That reduces operation load on air conditioners and saves electricity.

## Control and automation

- KOMFORT EC LB... S21** units are equipped with a build-in automation system. The remote control panel is not included in the delivery set (purchased separately).
- The S21 controller allows integrating the unit into the **Smart Home** system or **BMS (Building Management Systems)**.
- The unit can be controlled via the **Blauberg AHU** mobile application via Wi-Fi.



Download  
the **Blauberg AHU**  
app for Android



Download  
the **Blauberg AHU**  
app for iOS



- The **KOMFORT EC LB S14** units have an integrated control system with a wall-mounted control panel S14 with a LED indication.

## Air filtration

- Two built-in G4 and F7 filters provide efficient supply air filtration.
- The G4 filter is used for extract air filtration.

## Air heater

- The **KOMFORT EC LBE S21** units are equipped with an electric heater for additional heating of supply air downstream of the heat exchanger.
- The **KOMFORT EC LB S21** units are not equipped with built-in heaters but both a preheater and a reheater can be purchased separately.

## Bypass

- The **KOMFORT EC LB(E) S21** model is equipped with a bypass which is automatically opened in summer if there is a need to cool down the ventilated area with cool intake air.
- The **KOMFORT EC LB S14** unit is equipped with a bypass that is opened manually.
- If the unit is equipped with an electric heater, the bypass is used for freeze protection of the heat exchanger.

## Mounting

- Mounting on floor or ceiling with fixing brackets.
- The correct mounted unit must provide condensate collecting and drainage as well as access to service mounting and filter replacement.

## Automation functions

Functions	KOMFORT EC LB(E) S21	KOMFORT EC LB S14
Unit control via Wi-Fi using a mobile application	+	-
Unit control via a wired remote control panel	S22 control panel (option) 	S14 control panel 
Unit control via a wireless remote control panel	S22 WiFi control panel (option) 	-
Unit control via a wired remote LCD control panel	S25 control panel (option) 	-
	RS-485	-
BMS (Building Management Systems)	Wi-Fi	-
	Ethernet	-
	MODBUS (RTU, TCP)	-
Blauberg Cloud Server service	+	-
Speed selection	+	+
Filter replacement indication	according to hour meter readings according to filter clogging differential pressure switch readings	according to hour meter readings
Alarm indication	full alarm description in the mobile application	LED alarm indication
Week-scheduled operation	+	-
Bypass	automatic manual	manual
Timers	+	-
Boost mode	+	-
Fireplace mode	+	-
Freeze protection	through cyclic stops of the supply fan through preheating (option) using a bypass	through cyclic stops of the supply fan
Reheater connection	option	-
Cooler connection	option	-
Minimum supply air temperature control	+	-
Humidity control	option	option
CO2 controller	option	option
VOC controller	option	-
PM2.5 control	option	-
Fire alarm sensor connection	option	option


option: function is available when purchasing the appropriate accessory (see the "Accessories" section).

## Designation key

Series	Motor type	Spigot modification	Bypass	Heater type	Nominal air flow, [m³/h]	Heat exchanger type	Control
KOMFORT	EC: electronically commutated motor	L: horizontal spigot orientation	B: with a bypass	–: without a heater E: electric heater	300; 400; 700	–: heat recovery –E: energy recovery	S21 S14

## Overall dimensions [mm]

Model	Ø D	B	B1	H	L	L1
KOMFORT EC LB300(-E) S21/S14	157	566	480	479	1083	1180
KOMFORT EC LBE300(-E) S21/S14	157	566	480	479	1083	1180
KOMFORT EC LB400(-E) S21/S14	197	682	596	504	1094	1191
KOMFORT EC LBE400(-E) S21/S14	197	682	596	504	1094	1191
KOMFORT EC LB700(-E) S21/S14	247	866	700	601	1282	1379
KOMFORT EC LBE700(-E) S21/S14	247	866	700	601	1282	1379






## Technical data

Parameters	KOMFORT EC LB300 S21 KOMFORT EC LB300 S14	KOMFORT EC LBE300 S21	KOMFORT EC LB300-E S21 KOMFORT EC LB300-E S14	KOMFORT EC LBE300-E S21
Voltage [V / 50 (60) Hz]	1~ 230	1~ 230	1~ 230	1~ 230
Power (without a heater) [W]	182	182	182	182
Current (without a heater) [A]	1.4	1.4	1.4	1.4
Electric heater power [W]	-	2800	-	2800
Electric heater current [A]	-	12.2	-	12.2
Power (with a heater) [W]	182	2982	182	2982
Current (with a heater) [A]	1.4	13.6	1.4	13.6
Maximum air flow [m³/h (l/s)]	380 (106)	380 (106)	380 (106)	380 (106)
RPM [min⁻¹]	2100	2100	2100	2100
Sound pressure level at a distance of 3 m [dBA]	24	24	24	24
Transported air temperature [°C]	-25...+60	-25...+60	-25...+60	-25...+60
Casing material	galvanized steel	galvanized steel	galvanized steel	galvanized steel
Insulation	40 mm mineral wool	40 mm mineral wool	40 mm mineral wool	40 mm mineral wool
Extract filter	G4	G4	G4	G4
Supply filter	G4+F7	G4+F7	G4+F7	G4+F7
Connected air duct diameter [mm]	160	160	160	160
Weight [kg]	63.1	64.3	63.1	64.3
Heat recovery efficiency [%]	80–98	80–98	74–89	74–89
Heat exchanger type	counter-flow	counter-flow	enthalpy	enthalpy
Heat exchanger material	polystyrene	polystyrene	enthalpy	enthalpy
SEC class	A+	A+	A	A

Sound power level, A-weighted	Total	Octave band [Hz]								LpA 3 m [dBA]	LpA 1 m [dBA]
		63	125	250	500	1000	2000	4000	8000		
L <sub>WA</sub> to supply inlet [dBA]	67	50	55	56	62	60	62	56	50		
L <sub>WA</sub> to supply outlet [dBA]	53	42	47	46	46	44	39	29	21		
L <sub>WA</sub> to exhaust inlet [dBA]	68	56	54	61	62	59	61	56	50		
L <sub>WA</sub> to exhaust outlet [dBA]	55	42	47	51	48	46	43	31	22		
L <sub>WA</sub> to environment [dBA]	45	34	35	40	39	32	36	31	27	24	34

\* Data for point 1 in the performance diagram

Point	Power [W]	Sound pressure level at 3 m distance [dBA]
1	155	24 (34)
2	143	23 (33)
3	119	23 (33)
4	61	20 (30)
5	56	20 (30)
6	46	20 (30)
7	20	13 (23)
8	19	13 (23)
9	18	13 (23)




## Technical data

Parameters	KOMFORT EC LB400 S21 KOMFORT EC LB400 S14	KOMFORT EC LBE400 S21	KOMFORT EC LB400-E S21 KOMFORT EC LB400-E S14	KOMFORT EC LBE400-E S21
Voltage [V / 50 (60) Hz]	1~230	1~230	1~230	1~230
Power (without a heater) [W]	289	289	289	289
Current (without a heater) [A]	2.1	2.1	2.1	2.1
Electric heater power [W]	-	2800	-	2800
Electric heater current [A]	-	12.2	-	12.2
Power (with a heater) [W]	289	3089	289	3089
Current (with a heater) [A]	2.1	14.3	2.1	14.3
Maximum air flow [m³/h (l/s)]	540 (150)	540 (150)	540 (150)	540 (150)
RPM [min⁻¹]	2600	2600	2600	2600
Sound pressure level at a distance of 3 m [dBA]	27	27	27	27
Transported air temperature [°C]	-25...+40	-25...+40	-25...+40	-25...+40
Casing material	galvanized steel	galvanized steel	galvanized steel	galvanized steel
Insulation	40 mm mineral wool	40 mm mineral wool	40 mm mineral wool	40 mm mineral wool
Extract filter	G4	G4	G4	G4
Supply filter	G4+F7	G4+F7	G4+F7	G4+F7
Connected air duct diameter [mm]	200	200	200	200
Weight [kg]	74.8	76	74.8	76
Heat recovery efficiency [%]	84–98	84–98	78–89	78–89
Heat exchanger type	counter-flow	counter-flow	counter-flow	counter-flow
Heat exchanger material	polystyrene	polystyrene	enthalpy	enthalpy
SEC class	A+	A+	A	A


Sound power level, A-weighted	Total	Octave band [Hz]								LpA 3 m [dBA]	LpA 1 m [dBA]
		63	125	250	500	1000	2000	4000	8000		
L <sub>WA</sub> to supply inlet [dBA]	71	52	57	57	68	64	64	59	53		
L <sub>WA</sub> to supply outlet [dBA]	56	44	49	47	52	47	41	31	24		
L <sub>WA</sub> to exhaust inlet [dBA]	70	52	56	60	66	62	64	60	53		
L <sub>WA</sub> to exhaust outlet [dBA]	58	39	49	52	53	49	46	35	24		
L <sub>WA</sub> to environment [dBA]	48	32	37	40	45	36	38	35	30	27	37

\* Data for point 1 in the performance diagram

Point	Power [W]	Sound pressure level at 3 m distance [dBA]
1	240	27 (37)
2	215	26 (36)
3	196	26 (36)
4	89	21 (31)
5	80	21 (31)
6	72	20 (30)
7	27	19 (29)
8	26	19 (29)
9	24	17 (27)



KOMFORT EC LB(E)400



KOMFORT EC LB(E)400-E





## Technical data

Parameters	KOMFORT EC LB700 S21 KOMFORT EC LB700 S14	KOMFORT EC LBE700 S21	KOMFORT EC LB700-E S21 KOMFORT EC LB700-E S14	KOMFORT EC LBE700-E S21
Voltage [V / 50 (60) Hz]	1~ 230	1~ 230	1~ 230	1~ 230
Power (without a heater) [W]	336	336	336	336
Current (without a heater) [A]	2.4	2.4	2.4	2.4
Electric heater power [W]	-	3600	-	3600
Electric heater current [A]	-	15.6	-	15.6
Power (with a heater) [W]	336	3936	336	3936
Current (with a heater) [A]	2.4	18.0	2.4	18.0
Maximum air flow [m³/h (l/s)]	830 (231)	830 (231)	830 (231)	830 (231)
RPM [min⁻¹]	3200	3200	3200	3200
Sound pressure level at a distance of 3 m [dBA]	31	31	31	31
Transported air temperature [°C]	-25...+40	-25...+40	-25...+40	-25...+40
Casing material	galvanized steel	galvanized steel	galvanized steel	galvanized steel
Insulation	40 mm mineral wool	40 mm mineral wool	40 mm mineral wool	40 mm mineral wool
Extract filter	G4	G4	G4	G4
Supply filter	G4+F7	G4+F7	G4+F7	G4+F7
Connected air duct diameter [mm]	250	250	250	250
Weight [kg]	107	108.4	107	108.4
Heat recovery efficiency [%]	80–98	80–98	74–89	74–89
Heat exchanger type	counter-flow	counter-flow	enthalpy	enthalpy
Heat exchanger material	polystyrene	polystyrene	enthalpy	enthalpy
SEC class	A+	A+	A	A

Sound power level, A-weighted	Total	Octave band [Hz]								LpA 3 m [dBA]	LpA 1 m [dBA]
		63	125	250	500	1000	2000	4000	8000		
L <sub>WA</sub> to supply inlet [dBA]	76	56	61	61	73	69	69	64	57		
L <sub>WA</sub> to supply outlet [dBA]	60	49	53	52	56	51	44	34	26		
L <sub>WA</sub> to exhaust inlet [dBA]	74	56	60	65	70	66	68	64	56		
L <sub>WA</sub> to exhaust outlet [dBA]	61	42	53	56	56	52	49	37	25		
L <sub>WA</sub> to environment [dBA]	51	35	40	43	49	39	40	37	32	31	41

\* Data for point 1 in the performance diagram

Point	Power [W]	Sound pressure level at 3 m distance [dBA]
1	336	31 (41)
2	336	30 (40)
3	336	29 (39)
4	123	25 (35)
5	115	25 (35)
6	96	24 (34)
7	41	23 (33)
8	38	23 (33)
9	36	20 (30)



## Accessories

	KOMFORT EC LB 300(-E) S21	KOMFORT EC LB 300(-E) S14	KOMFORT EC LBE 300(-E) S21
Panel filter G4	 FP 484x178x48 G4	FP 484x178x48 G4	FP 484x178x48 G4
Panel filter F7	 FP 484x178x48 F7	FP 484x178x48 F7	FP 484x178x48 F7
Control panel	 S22	-	S22
Wi-Fi control panel	 S22 Wi-Fi	-	S22 Wi-Fi
LCD control panel	 S25	-	S25
Indoor humidity sensor	 FS2	FS2	FS2
CO <sub>2</sub> sensor with indication	 CD-1	CD-1	CD-1
CO <sub>2</sub> sensor	 CD-2	CD-2	CD-2
Humidity sensor	 HR-S	HR-S	HR-S
VOC sensor	 DPWQ30600	-	DPWQ30600
CO <sub>2</sub> sensor	 DPWQ40200	-	DPWQ40200
Humidity sensor	 DPWC11200	-	DPWC11200
Reheater	 ENH 160	-	-
Preheater	 EVH 160	-	EVH 160
Silencer	 SD 160	SD 160	SD 160
Silencer	 SDF 160	SDF 160	SDF 160
Non-return valve	 VRV 160	VRV 160	VRV 160
Air damper	 VKA 160	VKA 160	VKA 160
Drain pump	 CP-2	CP-2	CP-2
Air damper actuator	 LF230	LF230	LF230
Air damper actuator	 TF230	TF230	TF230

	KOMFORT EC LB 400(-E) S21	KOMFORT EC LB 400(-E) S14	KOMFORT EC LBE 400(-E) S21
Panel filter G4		FP 600x205x48 G4	FP 600x205x48 G4
Panel filter F7		FP 600x205x48 F7	FP 600x205x48 F7
Control panel		S22	–
Wi-Fi control panel		S22 Wi-Fi	–
LCD control panel		S25	–
Indoor humidity sensor		FS2	FS2
CO <sub>2</sub> sensor with indication		CD-1	CD-1
CO <sub>2</sub> sensor		CD-2	CD-2
Humidity sensor		HR-S	HR-S
VOC sensor		DPWQ30600	–
CO <sub>2</sub> sensor		DPWQ40200	–
Humidity sensor		DPWC11200	–
Reheater		ENH 200	–
Preheater		EVH 200	–
Silencer		SD 200	SD 200
Silencer		SDF 200	SDF 200
Non-return valve		VRV 200	VRV 200
Air damper		VKA 200	VKA 200
Drain pump		CP-2	CP-2
Air damper actuator		TF230	TF230
Air damper actuator		TF230	TF230

	KOMFORT EC LB 700(-E) S21	KOMFORT EC LB 700(-E) S14	KOMFORT EC LBE 700(-E) S21
Panel filter G4	 FP 784x253x48 G4	FP 784x253x48 G4	FP 784x253x48 G4
Panel filter F7	 FP 784x253x48 F7	FP 784x253x48 F7	FP 784x253x48 F7
Control panel	 S22	-	S22
Wi-Fi control panel	 S22 Wi-Fi	-	S22 Wi-Fi
LCD control panel	 S25	-	S25
Indoor humidity sensor	 FS2	FS2	FS2
CO <sub>2</sub> sensor with indication	 CD-1	CD-1	CD-1-
CO <sub>2</sub> sensor	 CD-2	CD-2	CD-2
Humidity sensor	 HR-S	HR-S	HR-S
VOC sensor	 DPWQ30600	-	DPWQ30600
CO <sub>2</sub> sensor	 DPWQ40200	-	DPWQ40200
Humidity sensor	 DPWC11200	-	DPWC11200
Reheater	 ENH 250	-	-
Preheater	 EVH 250	-	EVH 250
Silencer	 SD 250	SD 250	SD 250
Silencer	 SDF 250	SDF 250	SDF 250
Non-return valve	 VRV 250	VRV 250	VRV 250
Air damper	 VKA 250	VKA 250	VKA 250
Drain pump	 CP-2	CP-2	CP-2
Air damper actuator	 LF230	LF230	LF230
Air damper actuator	 TF230	TF230	TF230