

JC070075

RadiaLED Rapid

RadiaLED Rapid IP65 4000K 12W + With RIM

Features & Benefits

- 2.5x Faster to install than traditional LED bulkheads
- Detachable terminal, for simple wiring connection
- Multiply cable entry, central and offset rear entry points
- 20mm conduit entry, on top, bottom, sides and rim
- Clip-in tool-less LED gear tray design
- Smooth, even light distribution
- IK10, maximum impact rating
- IP65 protection against dust and moisture
- Emergency, microwave and dimmable options
- Complete with white rim as standard



BEAM















WARRANTY

General Information

Product Group

Product Range

Trade Name

Light Source

Light Source Features

IK Rating

Product Shape

Mounting

Product Weight

Color Finish

Overall Dimensions

Recommended Product Location

Method Of Fix

IP Rating

Environment

Suitable For Zones

LED-Surface

RadiaLED Rapid

RadiaLED

LED

Neutral White

IK10

Round

Wall or ceiling

1.2

White

Ø340 x 98.3

Suitable for interior and exterior applications for ceiling and wall

mounting

Back screw fix or BESA plate mounting

IP65

Demanding

Suitable for inside Zone 1

Luminaire Accessories JC070203 -4 security screws, JC070204 -Tool for RadiaLED Rapid

security screws. 5 rim options including eyelid

Distance From Lighted Object 0.3

Origin of manufacturer China

2 years standard warranty extends to 5 years when registered

Warranty within the first year of purchase (See Website for terms and

conditions)

Driver Manufacturer KG Power

LED Manufacturer/Type 3528/Nationstar

Lighting Product Type 1 Ceiling mount

Lighting Product Type 2 Wall light

Electrical

Voltage Rating 220-240

Secondary Running Current 300mA

Primary Running Current

Onerating Frequency Hz

50/60

CC or CV Constant Current

Luminaire Circuit Wattage 12

Sec - Voltage (V) **25-40**

Class II

EMC Compliant (EN55015) Yes

Power Factor Correction 0.5

Input Electrical Connections

Live, Neutral, with earth provision

Dimmable No

Thermals

Room Ambient Temperature 26°C

Max Driver/Ballast Ambient Temp. 45°C

Performance Data

LED Life (Hours) 60000

Hours life stated is an indication of expected L70 chip and light output calculations when operating in optimum conditions. Product warranty period supports the full product during the term given. The L70 hours expectancy is not correlated with the full product warranty term, nor is it a representation of lumen depreciation during the warranty period.

Energy Rating A++

Actual Lumen Output 1250

Lumens Per Circuit Watt 104

Standard Deviation Colour Matching - SDCM ≤ 6

Color Rendering Index 80-89

CRI: Ra 84

Correlated Color Temperature 4000

Light Distribution Detail 116
LOR (Light Output Ratio) % 100
Photometry Available Yes

Construction

Primary Material Polycarbonate

Outer Diffuser Polycarbonate

LED Brand Nationstar

Heat Sink PA6 nylon

Driver Housing Polycarbonate

Rim Or Attachment Polycarbonate

Packaging

Product Carton Dimensions 35 x 35 x 11 cm Product Packaged Weight 1.48 Quantity Per Outer Carton 8 72 Outer carton(L)- cm Outer carton(W)- cm 37 Outer carton(H)- cm 46.5 Outer carton overall dimensions 72 x 37 x 46.5cm Outer carton Net weight-kg 11.84 Outer carton Gross weight- kg 12.51

Standards & Approvals

Product Bar Code EAN-13 Number

Outer carton Bar Code ITF-14 Number

Manufactured In Accordance To

CE Marked

BS EN 60598-2-1

Yes

Date code/Purchase order No.

Yes

WEEE Symbol


Yes

Certificate Of Conformity Available on request

Accredited Members LIA, ISO9001:2015, ISO14001:2015

5052544106217

15052544106214

















JCC Lighting LTD Innovation Centre, Beeding Close, Southern Cross Trading Estate, Bognor Regis, West Sussex PO22 9TS Sales: 01243 838999 (8am to 5pm Monday to Friday) Fax: 01243 838998 | sales@jcc.co.uk | www.jcc.co.uk |

This document is uncontrolled if printed, all information is subject to change

Version 44 [23 Sep 2020]