

JC130003

Wall Pack

20W LED Commercial Wall Bulkhead Photocell

Features & Benefits

- IP65 protection
- IK08 rated



CLASS I



CRI:RA



RATING



SENSING



WARRANTY

General Information

Product Group

LED Bulkhead

Product Range

LED Commercial Wall Bulkhead

Light Source

LED

Light Source Features

Neutral White

Mounting

Wall mounted

Product Weight

1kg

Color Finish

Black

Overall Dimensions

222 x 206 x 85mm

Recommended Product Location

Suitable for interior and exterior

Method Of Fix

Back screw fix

IP Rating

IP65

Environment

Demanding

Suitable For Zones

Suitable for inside Zone 1

Origin of manufacturer

China

Warranty

2 years standard warranty extends to 5 years when registered within the first year of purchase (See Website for terms and conditions)

Driver Manufacturer

Ding Sheng

LED Manufacturer/Type

Derunda Optoelectronics

Lighting Product Type 1

Wall Mount

Electrical

Voltage Rating	100-240V~
Secondary Running Current	600mA
Primary Running Current	0.8A
Operating Frequency Hz	50/60Hz
CC or CV	Constant current
Luminaire Circuit Wattage	20W
Sec - Voltage (V)	24-40Vdc
Class	Class I
Total Harmonic Distortion (THD)%	10%
EMC Compliant (EN55015)	Yes
Power Factor Correction	0.95
Input Electrical Connections	Live, neutral, earth
Dimmable	No
Photocell/PIR compatable	Yes

Thermals

Room Ambient Temperature	25°C
Max Driver/Ballast Ambient Temp.	85°C

Performance Data

Hours life stated is an indication of expected L70 chip and light output calculations when operating in optimum conditions.Product warranty period supports the full product during the term given. The L70 hours expectancy is not correlated with thefull product warranty term, nor is it a representation of lumen depreciation during the warranty period.

Actual Lumen Output	1750
Lumens Per Circuit Watt	87
CRI: Ra	72
Correlated Color Temperature	4000
Photometry Available	Yes

Controls and Sensors

Lux Settings	On: 10-20lux Off: 30-80lux
--------------	----------------------------

Construction

Primary Material	Aluminium
Outer Diffuser	Polycarbonate
Driver Housing	Polycarbonate

Packaging

Product Carton Dimensions	22 x 9 x 23cm
---------------------------	---------------

Product Packaged Weight	1.15kg
Quantity Per Outer Carton	8
Outer carton(L)- cm	46cm
Outer carton(W)- cm	37.5cm
Outer carton(H)- cm	25cm
Outer carton overall dimensions	46 x 37.5 x 25cm
Outer carton Net weight- kg	9.24kg
Outer carton Gross weight- kg	9.94kg
Product Bar Code EAN-13 Number	5052544106040
Outer carton Bar Code ITF-14 Number	15052544106047

Standards & Approvals

Manufactured In Accordance To	BS EN 60598-2-1
CE Marked	Yes
Date code/Purchase order No.	Yes
WEEE Symbol	Yes
Certificate Of Conformity	Available on request
Accredited Members	LIA, ISO9001:2015, ISO14001:2015



