

# JC130006

## Wall Pack

30W LED Commercial Wall Bulkhead Photocell

### Features & Benefits

- IP65 protection
- IK08 rated
- Emergency option available



CLASS I



CRI:RA



SENSING



WARRANTY

### General Information

Product Group

**LED Bulkhead**

Product Range

**LED Commercial Wall Bulkhead**

Light Source

**LED**

Light Source Features

**Neutral White**

Mounting

**Wall mounted**

Product Weight

**2.15kg**

Color Finish

**Black**

Overall Dimensions

**308 x 288 x 126mm**

Recommended Product Location

**Suitable for interior and exterior**

Method Of Fix

**Back screw fix**

IP Rating

**IP65**

Environment

**Demanding**

Suitable For Zones

**Suitable for inside Zone 1**

Origin of manufacturer

**China**

Warranty

**2 years standard warranty extends to 5 years when registered within the first year of purchase (See Website for terms and conditions)**

Driver Manufacturer

**Ding Sheng**

LED Manufacturer/Type

**Derunda Optoelectronics**

Lighting Product Type 1

**Wall Mount**

## Electrical

Voltage Rating	100-240V~
Secondary Running Current	900mA
Primary Running Current	1.0A
Operating Frequency Hz	50/60Hz
CC or CV	Constant current
Luminaire Circuit Wattage	30W
Sec - Voltage (V)	20-36Vdc
Class	Class I
Total Harmonic Distortion (THD)%	10%
EMC Compliant (EN55015)	Yes
Power Factor Correction	0.95
Input Electrical Connections	Live, neutral, earth
Dimmable	No
Photocell/PIR compatible	Yes

## Thermals

Room Ambient Temperature	25°C
Max Driver/Ballast Ambient Temp.	85°C

## Performance Data

Hours life stated is an indication of expected L70 chip and light output calculations when operating in optimum conditions. Product warranty period supports the full product during the term given. The L70 hours expectancy is not correlated with the full product warranty term, nor is it a representation of lumen depreciation during the warranty period.

Actual Lumen Output	2600
Lumens Per Circuit Watt	87
CRI: Ra	72
Correlated Color Temperature	4000
Photometry Available	Yes

## Controls and Sensors

Lux Settings	On: 10-20lux Off: 30-60lux
--------------	----------------------------

## Construction

Primary Material	Aluminium
Outer Diffuser	Polycarbonate
Driver Housing	Polycarbonate

## Packaging

Product Carton Dimensions	30.5 x 13 x 31.5cm
---------------------------	--------------------

Product Packaged Weight	<b>2.25kg</b>
Quantity Per Outer Carton	<b>4</b>
Outer carton(L)- cm	<b>54.5cm</b>
Outer carton(W)- cm	<b>33cm</b>
Outer carton(H)- cm	<b>33.5cm</b>
Outer carton overall dimensions	<b>54.5 x 33 x 33.5cm</b>
Outer carton Net weight- kg	<b>9.42kg</b>
Outer carton Gross weight- kg	<b>10.16kg</b>
Product Bar Code EAN-13 Number	<b>5052544106071</b>
Outer carton Bar Code ITF-14 Number	<b>15052544106078</b>

## Standards & Approvals

Manufactured In Accordance To	<b>BS EN 60598-2-1</b>
CE Marked	<b>Yes</b>
Date code/Purchase order No.	<b>Yes</b>
WEEE Symbol	<b>Yes</b>
Certificate Of Conformity	<b>Available on request</b>
Accredited Members	<b>LIA, ISO9001:2015, ISO14001:2015</b>



