Affresco Discreet Wall Fans (100, 125 & 150mm)



Basic, Timer or pull cord controls options

Easy to install

Suitable for bathroom zones 1, 2 & 3 Low profile

Accessories

ED1/ED150

Easyfix ducting plastic wall liner with integral screw-fixing channels.



FF100

Fast fix wall duct system. Comprises 100mm PVC duct with external wall duct seal and external grille.



FG1/FG2

Complementary fixed blade louvred grille in semi-matt ABS plastic. White or brown grille.



Physical Specifications


Weiaht:

100mm – 0.54kg 125mm – 0.65kg


150mm – 0.76kg

Material: ABS plastic

Dimensions



Performance Graph



Electrical Specifications

230V~50Hz class II

Consumption: 100mm Fan - 15W

125mm Fan – 23W 150mm Fan – 25W

Cabling: 1mm² max.

Data Table

	Performo BS 848 Pt1 i m³/h ⁻¹		ound Pressu level @ 3m dB(A)		Operation	Features
D100B\	N 97	27	38	24	Single speed	100mm induct wall fan with plain white front cover
D100TV	V 97	27	38	24	Single speed	100mm induct wall fan with timer and plain white front cover
D125B\	W 180	50	39	24	Single speed	125mm induct wall fan with plain white front cover
D125TV	V 180	50	39	24	Single speed	125mm induct wall fan with timer and plain white front cover
D150B\	N 298	83	40	24	Single speed	150mm induct wall fan with plain white front cover
D150TV	V 298	83	40	24	Single speed	150mm induct wall fan with timer and plain white front cover