

JC091001

Niteflood® LED Floodlights

Niteflood™ LED Floodlight 10W IP65 4000K Black

Features & Benefits

- Up to 112 LpcW
- IP65 protection against dust and moisture
- 60° angled bracket for ease of installation
- Breather gland incorporated to protect against condensation
- Opal glass for reduced glare
- Supplied pre-wired with 800mm flex
- Driverless technology
- PIR versions, with manual override available
- This product contains a light source of energy efficiency class E













General Information

Mounting Wall Mount

Environment **Exterior**

Product Group LED Floodlights

Color Finish Black

Product Shape Rectangular

Product Range Niteflood®

1010 1050 50

Overall Dimensions 104.2 x 125.6 x 53.4

Width (mm) 125.6

Height (mm) 104.2

Depth (mm) 53.4

Product Weight(kg) 0.298

Light Source LED

Recommended Product Location Exterior Wall Mount for security lighting

Method Of Fix Screws/Rawl plugs

Fixing Centres See profile drawing

IP Rating IP65
Origin of manufacturer China

Warranty (See Website for terms and conditions)

2.5m max Mounting Height

Driver Manufacturer No driver, mains LED Chips

LED Manufacturer/Type Smalite 2835

Customs Tariff code** 9405421000

Electrical

Voltage Rating 220-240

Operating Frequency Hz 50/60Hz

Luminaire Circuit Wattage 10

Ī

EMC Compliant (EN55015)

Power Factor Correction 0.9

Input Electrical Connections Live, Earth, Neutral

Performance Data

LED Life (Hours)* 54000

This product contains a light source of energy efficiency **Energy Rating**

Yes

class E

1000 Actual Lumen Output

Lumens Per Circuit Watt 100

Standard Deviation Colour Matching - SDCM <5

Color Rendering Index 80-89

83 CRI: Ra

4000 Correlated Color Temperature

Beam Angle° 100

LOR (Light Output Ratio) % 100

Photometry Available Yes, available on request

Construction

Primary Material Aluminium

Outer Diffuser Opal toughened glass

Heat Sink Aluminium

Packaging

Product carton overall dimensions(cm) 12.9 x 5.3 x 10.7cm

Product Packaged Weight(kg) 0.34

Quantity Per Outer Carton 20

Outer carton(L)- cm 36.8

Outer carton(W)-cm 27.9

Outer carton(H)- cm 16.2

Outer carton Net weight-kg 5.96

Outer carton Gross weight-kg 6.44

Product Bar Code EAN-13 Number 5052544109652

Outer carton Bar Code ITF-14 Number 15052544109659

Standards & Approvals

Manufactured In Accordance To

CE Marked

UKCA Marked

Date code/Purchase order No.

WEEE Symbol

Certificate Of Conformity

Accredited Members

BS EN 60598-2015,2-1,2-5

Yes


Yes

Yes


Yes


Available on request

LIA, ISO9001-2015, ISO14001-2015











*Hours life stated is an indication of expected L70 chip and light output calculations when operating in optimum conditions. Product warranty period supports the full product during the term given. The L70 hours expectancy is not correlated with the full product warranty term, nor is it a representation of lumen depreciation during the warranty period.

**JCC Lighting Limited makes every effort to ensure that the Customs Tariff information in this document is timely and accurate. However, it's not possible for us to assure the absolute veracity and completeness of that information, as errors may occur. The placement of any inaccurate tariff information is completely unintentional. JCC Lighting Limited reserves the right, in its sole discretion, to correct any errors or omissions to the tariff code and to make any and all changes contained in this document at any time and without notice. It is the sole responsibility of the importer to ensure that the commodity code advised is correct for the products/goods being supplied by JCC Lighting Limited. JCC Lighting Limited does not assume any liabilities, losses, costs, and expenses arising out of or related to the importers use of this commodity code or the information related to the import of any JCC Lighting products.

Company Registration Number: 03044848 | VAT Number: 918544112

This document is uncontrolled if printed, all information is subject to change

Version 186 [27/10/2023]