



a **LEVITON**
company

JC100005

Skypack QR High Output 4ft Single IP20 4000K 32W 4000lm Emergency



Features & Benefits

- Intelligent press release buttons for simple installation
- Ultra efficient, up to 125 lumens per circuit Watt
- Suspended LED tray for easy installation
- Press fit terminals, loop in loop out
- Rear and end conduit entry points
- Microwave dimmable options

General Information

Product Group	LED - Surface
Product Range	Skypack™
Trade Name	Skypack™ QR High Output
Light Source	LED
Light Source Features	White
Lighting Product Type	Linear Lighting
Lighting Product Type	Emergency Lighting
Product Shape	Rectangular
Mounting	Surface Mounted
Product Weight	2.62kg
Color Finish	White

JCC Lighting

Innovation Centre, Beeding Close, Southern Cross
Trading Estate, Bognor Regis, West Sussex, PO22 9TS
Company Registration Number: 03044848 | VAT Number: 918544112

T: 01243 838999 | F: 01243 838998 | sales@jcc.co.uk | www.jcc.co.uk

Overall Dimensions	1200 x 70 x 76.5
Recommended Product Location	Domestic, Commercial and Industrial Applications
Method Of Fix	Surface with Conduit Entry
IP Rating	IP20
Environment	Indoor
Origin Of Manufacture	Made In China
Warranty	2 years standard warranty extends to 5 years when registered within the first year of purchase (2 years on batteries)(See Website for terms and conditions)
Driver Manufacturer	Ledtu
LED Manufacturer/Type	Runlite 2835

Electrical

Voltage Rating	220-240
Secondary Running Current	730mA
Primary Running Current	250mA
Operating Frequency (Hz)	50/60Hz
CC or CV	Constant Current
Luminaire Circuit Wattage	32
Class	Class I
Output Voltage (V)	27-45VDC
Total Harmonic Distortion (THD)%	20%
EMC Compliant (EN55015)	Yes
Power Factor Correction	>0.9
Input Electrical Connections	Switched Live, Unswitched Live, Earth & Neutral
Dimmable	No

Emergency Data

Load Voltage	20-60VDC
Nominal Battery Current	2600mAh
Recharge Time	24 hours
Battery Specification	7.4V 2600mAh Li-ion
Battery Type	Li-ion
Battery Life In Emergency Mode	3 hours
Charge Current	200mA
DDP Protection	Yes, 6V
LOR In Emergency Mode	16%
Inverter PFC	0.5

Performance Data

Energy Rating	A+
Actual Lumen Output	4000

JCC Lighting

Innovation Centre, Beeding Close, Southern Cross
Trading Estate, Bognor Regis, West Sussex, PO22 9TS
Company Registration Number: 03044848 | VAT Number: 918544112

T: 01243 838999 | F: 01243 838998 | sales@jcc.co.uk | www.jcc.co.uk

Lumens Per Circuit Watt	125
LED Life (Hours) (L70)	54000
	Hours life stated is an indication of expected L70 chip and light output calculations when operating in optimum conditions. Product warranty period supports the full product during the term given. The L70 hours expectancy is not correlated with the full product warranty term, nor is it a representation of lumen depreciation during the warranty period.
Color Rendering Index	80-89
CRI: Ra	80
Correlated Color Temperature	4000K
Light Distribution Detail	120-degree
LOR (Light Output Ratio) %	100
Photometry Available	Yes

Construction

Primary Material	Steel
Outer Diffuser	Polycarbonate

Packaging


Quantity Per Outer Carton	8
Bar Code EAN Number	5052544104503

Standards & Approvals

Listings	CE
Listings	RoHS
Manufactured In Accordance To	BS EN 60598:2015, 2-1, 2-22
CE Marked	Yes
WEEE Symbol	Yes
Certificate Of Conformity	Yes: available on request.
Accredited Members	LIA, ISO9001:2015, ISO14001:2015

JCC Lighting

Innovation Centre, Beeding Close, Southern Cross
Trading Estate, Bognor Regis, West Sussex, PO22 9TS
Company Registration Number: 03044848 | VAT Number: 918544112
T: 01243 838999 | F: 01243 838998 | sales@jcc.co.uk | www.jcc.co.uk



JCC Lighting

Innovation Centre, Beeding Close, Southern Cross
Trading Estate, Bognor Regis, West Sussex, PO22 9TS
Company Registration Number: 03044848 | VAT Number: 918544112
T: 01243 838999 | F: 01243 838998 | sales@jcc.co.uk | www.jcc.co.uk