

LED200FLWHP

17W LED Compact Floodlight Twin Flood – White



Features & Benefits

- 2x 8.5W Powerful LED compact twin floodlight.
- 2x 1000 lumen bright white light.
- Pan and tilt light aiming adjustment (per head).
- Opal Diffuser for a even light distribution.
- Rear & bottom cable entry.
- Full polycarbonate lightweight housing.
- Back box or wall mountable.
- New intergrated Samsung SMD chipsets for added
- reliability and efficient heat dissipation.
- IP55 Weatherproof rating.

Technical Data

| | |
|---------------------------|-----------------------------|
| Operating Voltage | 230V AC |
| Frequency | 50Hz |
| Installation Type | Surface Mount |
| Earth Class Rating | Class II |
| Operating Temperature | -20°C to 50°C |
| Ingress Protection Rating | IP55 |
| Wattage | 17 |
| Beam Angle | 98° x 98° (Per Head) |
| Pan & Tilt Adjustment | Pan Left 40°, Pan Right 40° |
| Energy Efficiency | Class D |
| Energy Usage | 17Kwh/1000H |

Data sheet

LED200FLWHP

Light / LED Lighting

| | |
|----------------------------|--------------------------------------|
| Lumen output (lm) | 2000 |
| Luminaire Efficiency | 118 lm/W |
| Colour Temperature (K) | 4000 |
| LED Type | SMD (Integrated) |
| Mounting Hole Centres (mm) | 60 |
| Multiple Unit Support | Yes |
| Cable Entry(s) | Bottom Entry (Knockouts), Back Entry |

General

| | |
|-----------------------------|------------------------|
| Weight (g) | 300 |
| Height (mm) | 160 |
| Width (mm) | 167 |
| Depth (mm) | 50 |
| Body Construction | Polycarbonate |
| Product Colour | White |
| Accessories (Included) | Fittings, Setting Knob |
| EAN Number | 5012483015834 |
| Guarantee Period | 3 Years |
| Trade Tariff Commodity Code | 9405114090 |

Line Diagrams

