

Sensor-switched LED outdoor light

L 220 S

Stainless steel

EAN 4007841 010454

Article number 010454



LED

30 years (Ø 4,5h / day)

3000 K

3000K warm-white



infrared sensor
180°



max. 10 m



IP44



2 - 2000 lux



8 sec - 35 min



Light source not
exchangeable



Control gear not
exchangeable



shock proof IK07

Function description

Light with informative value. Modern L 220 S sensor-switched LED outdoor light with large, square front surface for self-adhesive house numbers. Inviting, soft ambient light for entrances. Light output of 869 lm at a power consumption of only 9,3 W. 180° angle of coverage, 10 m reach.

L 220 S

Stainless steel
 EAN 4007841 010454
 Article number 010454



Technical specifications

Dimensions (L x W x H)	84 x 246 x 251 mm
With lamp	Yes, STEINEL LED system
Manufacturer's Warranty	3 years
Settings via	Potentiometers
With remote control	No
Version	Stainless steel
PU1, EAN	4007841010454
Application, place	Outdoors
Application, room	outdoors, front door, all round the building, terrace / balcony, courtyard & driveway
Colour	Stainless steel
includes sheet of self-adhesive numbers	Yes
Installation site	wall
Impact resistance	IK07
IP-rating	IP44
Protection class	II
Ambient temperature	-20 – 50 °C
Housing material	Stainless steel
Cover material	Plastic, opal
Mains power supply	220 – 240 V / 50 – 60 Hz
Output	9,3 W
Average rated life expectancy of power supply unit at 25°C	> 60000 h
Mounting height max.	3,00 m
Slave modeselectable	No
Sneak-by guard	Yes
Capability of masking out individual segments	Yes

Electronic scalability	No
Mechanical scalability	No
Reach, radial	r = 3 m (14 m ²)
Reach, tangential	r = 10 m (157 m ²)
Photo-cell controller	Yes
Cover material	sticker
Luminous flux total product	869 lm
Measured luminous flux (360°)	869 lm
Total product efficiency	93 lm/W
Colour temperature	3000 K
Colour variation LED	SDCM3
Lamp	LED cannot be replaced
Service life LED L70B50 (25°)	> 60000 h
Base	without
LED cooling system	Passive Thermo Control
Soft light start	No
Twilight setting	2 – 2000 lx
Time setting	8 s – 35 Min.
Basic light level function	No
Main light adjustable	No
Interconnection	No
Colour Rendering Index CRI	= 82
Optimum mounting height	2 m
Detection angle	180 °

Sensor-switched LED outdoor light

L 220 S


Stainless steel

EAN 4007841 010454

Article number 010454



Detection Zone




Possible mounting height: 1,80 m - 3,00 m

Orange: radial

Black: tangential

Dimension Drawing



Circuit diagram

