


Ducting - Adaptors

Elbow 90° Bend M to F


Connector for joining Round Pipe, Flexi Hose & Flat Channel Ducting



Cat. No.	Product Type	External Dimensions			Resistance (Pa) at flow rate								
		H	W	D	8 l/s	13 l/s	21 l/s	29 l/s	37 l/s	45 l/s	53 l/s	61 l/s	
40300	100mmØ to 110 x 54mm	90	115	140	3	8	17.7	33	49.9	74.5	101	137	
58400	125mmØ to 150 x 70mm	-	-	-	-	-	-	-	-	-	-	-	
54400	100mmØ to 204 x 60mm	80	215	195	2.9	7.1	15.1	28	45.1	68.1	92.2	118	
55400	125mmØ to 204 x 60mm	80	215	195	3.1	5.9	12.2	25	43.6	62.2	86	111	
56400	150mmØ to 204 x 60mm	80	215	195	2.8	4.9	11.6	21	31	41	53	67	
60941	100mmØ to 220 x 90mm	118	226	240	-	-	-	-	-	-	-	-	
60951	125mmØ to 220 x 90mm	118	226	240	-	-	-	-	-	-	-	-	
60961	150mmØ to 220 x 90mm	11	226	240	-	-	-	-	-	-	-	-	

Short to Round Rectangular Adaptor

with male/female adaptors for Connecting Flat Channel Ducting to Round Hose



Cat. No.	Product Type	External Dimensions			Resistance (Pa) at flow rate								
		H	W	D	8 l/s	13 l/s	21 l/s	29 l/s	37 l/s	45 l/s	53 l/s	61 l/s	
40700	100mm to 110 x 54mm (F)	60	110	105	1.2	4.3	8.4	20	30.2	43	62	88	
40710	100mm to 110 x 54mm (M)	60	110	105	1.2	4.3	8.4	20	30.2	43	62	88	

Round to Rectangular Adaptor - Adaptor to Connect Flat Channel Ducting



Cat. No.	Product Type	External Dimensions			Resistance (Pa) at flow rate								
		H	W	D	8 l/s	13 l/s	21 l/s	29 l/s	37 l/s	45 l/s	53 l/s	61 l/s	
40701	100mmØ to 110 x 54mm	100	115	180	1.2	4.2	8.3	19.8	29.9	42	60	86	
58701	125mmØ to 150 x 70mm	-	-	-	-	-	-	-	-	-	-	-	
55710	100mmØ to 204 x 60mm	140	210	215	1.0	1.96	3.2	4.9	6.7	8.7	11.2	14.5	
55700	125mmØ to 204 x 60mm	140	210	213	<1	<1	1.5	2.8	4.5	6.7	9	11.5	
60970	150mmØ to 220 x 90mm	160	225	203	-	-	-	-	-	-	-	-	


Adaptor - Adaptor to Connect Round Pipe Ducting



Cat. No.	Product Type	External Dimensions			Resistance (Pa) at flow rate								
		H	W	D	8 l/s	13 l/s	21 l/s	29 l/s	37 l/s	45 l/s	53 l/s	61 l/s	
54544	125mm to 100mm	-	-	-	-	-	-	-	-	-	-	-	

Offset Reducer


Adaptor to Connect Round Pipe Ducting



Cat. No.	Product Type	External Dimensions			Resistance (Pa) at flow rate								
		H	W	D	8 l/s	13 l/s	21 l/s	29 l/s	37 l/s	45 l/s	53 l/s	61 l/s	
45644	150mm to 125mm or 100mm	-	-	-	-	-	-	-	-	-	-	-	

Circular Reducer

Adaptor to Connect Round Pipe Ducting, Flexi Hose & Fan Spigots



Cat. No.	Product Type	External Dimensions			Resistance (Pa) at flow rate								
		H	W	D	8 l/s	13 l/s	21 l/s	29 l/s	37 l/s	45 l/s	53 l/s	61 l/s	
54119	125mm to 100mm	-	-	-	-	-	-	-	-	-	-	-	
65118	150mm to 125mm	-	-	-	-	-	-	-	-	-	-	-	
86117	200mm to 150mm	-	-	-	-	-	-	-	-	-	-	-	
98116	250mm to 200mm	-	-	-	-	-	-	-	-	-	-	-	
12800	300mm to 200mm	-	-	-	-	-	-	-	-	-	-	-	
40419	110mm to 100mm	-	-	-	-	-	-	-	-	-	-	-	

Rubber Spigot Adaptor - Adaptor to Connect Cookerhood Spigots




Cat. No.	Product Type	External Dimensions			Resistance (Pa) at flow rate								
		H	W	D	8 l/s	13 l/s	21 l/s	29 l/s	37 l/s	45 l/s	53 l/s	61 l/s	
50519	120mm to 125mm	-	-	-	-	-	-	-	-	-	-	-	

Plenum Cooker Hood/Fan - with Connector



Cat. No.	Product Type	External Dimensions			Resistance (Pa) at flow rate								
		H	W	D	8 l/s	13 l/s	21 l/s	29 l/s	37 l/s	45 l/s	53 l/s	61 l/s	
1640	100mm to 225mm	-	-	-	-	-	-	-	-	-	-	-	
1650	100mm to 300mm	-	-	-	-	-	-	-	-	-	-	-	
1645	120mm to 225mm	-	-	-	-	-	-	-	-	-	-	-	
1655	120mm to 300mm	-	-	-	-	-	-	-	-	-	-	-	

Round to Rectangular Adaptor - Requires 414C Connector



Cat. No.	Product Type	External Dimensions			Resistance (Pa) at flow rate								
		H	W	D	8 l/s	13 l/s	21 l/s	29 l/s	37 l/s	45 l/s	53 l/s	61 l/s	
40725	100mm to 225 x 25mm	-	-	-	-	-	-	-	-	-	-	-	
40730	105mm to 300 x 25mm	-	-	-	-	-	-	-	-	-	-	-	