

Monsoon Compact Cased Axial Fans

- Die cast aluminium blade & external rotor motor design
- Motors dynamically balanced to ISO 1940 & IP54 protected
- Motor insulation Class F
- Temperature operation -40° to +70°
- Thermal overload for motor protection
- Terminal box IP54 protection



Single Phase 4 Pole

CODE	DESCRIPTION
EF-25-WA	250mm (756m ³ /h)
EF-31-2A	315mm (2,052m ³ /h)
EF-35-2C	355mm (3,456m ³ /h)
EF-40-4C	400mm (5,040m ³ /h)
EF-45-4C	450mm (6,192m ³ /h)
EF-50-4F	500mm (7,560m ³ /h)
EF-56-6K	560mm (13,392m ³ /h)
EF-63-6N	630mm (18,324m ³ /h)

Three Phase 4 Pole

CODE	DESCRIPTION
DF-31-2A	315mm (2,088m ³ /h)
DF-35-2C	355mm (3,600m ³ /h)
DF-40-2F	400mm (5,328m ³ /h)
DF-45-4C	450mm (6,480m ³ /h)
DF-50-4F	500mm (8,172m ³ /h)
DF-56-6F	560mm (12,348m ³ /h)
DF-63-6K	630mm (18,684m ³ /h)

Wire Guard

CODE	DESCRIPTION
RFWG250	250mm Wire Guard
RFWG315	315mm Wire Guard
RFWG355	355mm Wire Guard
RFWG400	400mm Wire Guard
RFWG450	450mm Wire Guard
RFWG500	500mm Wire Guard
RFWG560	560mm Wire Guard
RFWG630	630mm Wire Guard

Cased Axial Accessories

Ancillary Pack

Consists of mounted feet (x2), AV mounts, 2 coupling flanges, 2 flex connectors and 4 worm drive clips

CODE	DESCRIPTION
RFAP250	350mm
RFAP315	315mm
RFAP355	355mm
RFAP400	400mm
RFAP450	450mm
RFAP500	500mm
RFAP560	560mm
RFAP630	630mm

Mounting Feet (x2)

CODE	DESCRIPTION
RFMF250	250mm Mounting Feet
RFMF315	315mm Mounting Feet
RFMF355	355mm Mounting Feet
RFMF400	400mm Mounting Feet
RFMF450	450mm Mounting Feet
RFMF500	500mm Mounting Feet
RFMF560	560mm Mounting Feet
RFMF630	630mm Mounting Feet

Coupling Flange

CODE	DESCRIPTION
RFCF250	250mm Coupling Flange
RFCF315	315mm Coupling Flange
RFCF355	355mm Coupling Flange
RFCF400	400mm Coupling Flange
RFCF450	450mm Coupling Flange
RFCF500	500mm Coupling Flange
RFCF560	560mm Coupling Flange
RFCF630	630mm Coupling Flange