LED floodlight without sensor

Spot ONE

without motion detector EAN 4007841 058623 Article number 058623







Function description

Spot on! The purist swivelling LED wall spot ONE in aluminium comes with timeless aesthetic appeal for selective lighting all around the building. Can be interconnected with the "Spot ONE Sensor" master version by cable or simply used on its own as a powerfully bright individual solution. 512 lm light output from only 6,7 W. Includes lamp (GU-10-LED).

Technical specifications

Dimensions (L x W x H)	175 x 97 x 98 mm	Housing material	Aluminium
With lamp	Yes, LED lamp	Cover material	Plastic, transparent
With motion detector	No	Mains power supply	220 – 240 V / 50 – 60 Hz
Manufacturer's Warranty	3 years	Mechanical scalability	No
Version	without motion detector	Luminous flux total product	512 lm
PU1, EAN	4007841058623	Measured luminos flux (360°)	512 lm
Application, place	Outdoors	Total product efficiency	76,4 lm/W
Application, room	outdoors, all round the building, terrace / balcony, courtyard & driveway	Colour temperature	3000 K
		Colour variation LED	SDCM5
Colour	Anthracite	Lamp	LED can be replaced
Includes corner wall mount	No	Soft light start	No
Installation site	wall	Basic light level function	No
Installation	Wall, Surface wiring	Main light adjustable	No
Impact resistance	IK03	Interconnection	No
IP-rating	IP44	Output	6,7 W
Protection class		Colour Rendering Index CRI	= 81
Ambient temperature	-20 - 40 °C		


LED floodlight without sensor

Spot ONE without motion detector

EAN 4007841 058623 Article number 058623



Dimension Drawing





Circuit diagram

Master/slave interconnection circuit diagram

