

## BCAB-L CP 17-20 COMBI 304 BK



Products may differ in size, colour and appearance to those shown. If you require further information or customisation, please contact us directly.

### Type

BCAB-L CP 17-20 COMBI 304 BK

### WISKA-Order no.

10110935

### Description:

#### BC-KIT 6 Includes:

10 x EBFS 17-20/ 2 x COMBI 304/ 10m BCAB-L 17/ 10 x EMUG 20

#### Technical description of components:

EBFS 17-20 - Material number 10106867

Material Conduit fitting polyamide UL94-V0

Material Connection thread polyamide UL94-V0

Material sealing gasket TPU

Protection class IP66, IP68

Temp. range min -40 °C

Temp. range max 100 °C

Operational areas EN 45545 - Railway

NW 17

Thread type M

Ø Connection thread D 20

Lead 1,5

Length screw-in thread L 12 mm

Ø closure VD 32,7 mm

Ø inside 14,8 mm

Key width SW 27 mm

Total length TL 41,5 mm

Type of conduit fitting straight

UL 1696 Yes

Product Color RAL 9005

#### Your Contact:

#### WISKA UK Ltd.

Unit 7, Hurling Way · St. Columb Major Business Park · TR9 6SX, St. Columb Major, Cornwall · Great Britain

☎ +44-12-08816062 · 📠 +44-12-08816708

info@wiska.co.uk · www.wiska.co.uk

## COMBI 304 - Material number 10110630

Material Polypropylene  
Material sealing gasket TPE  
Temp. range min -30 °C  
Temp. range max 100 °C  
Temperatures during install. -5 °C - 60 °C  
Protection class IP66 / IP67  
Glow wire test 750 °C  
Voltage 400 V  
Rated cross section 2,5 mm<sup>2</sup>  
Fixing 2 external mounting feet  
Ø cable diameter min 3 mm  
Ø cable diameter max 12 mm  
External dimensions LxWxH Ø 82 x 57mm  
Type of cable gland M 20 x 1,5  
Product Color RAL 9005

## BCAB-L 17 - Material number 10109185

Material PA6 UL94-HB  
Temp. range min -40 °C  
Temp. range max 140 °C  
Product Color RAL 9005  
NW 17  
External diameter ED 21,2 mm  
Ø inside 16,8 mm  
Profile width A 3,3 mm  
Width B 2,3 mm  
Bending radius R 50 mm  
Wall thickness S 0,3 mm  
Model light

## EMUG 20 - Material number 10061782

Material Polyamide, fibre reinforced  
Temp. range min -40 °C  
Temp. range max 100 °C  
Glow wire test 650 °C  
Thread type M  
Ø Connection thread D 20  
Lead 1,5  
Key width SW 27 mm  
Collar diameter (E) 29 mm  
Total length TL 5 mm  
Product Color RAL 9005

25.10.2023

Your Contact:

WISKA UK Ltd.

Unit 7, Hurling Way · St. Columb Major Business Park · TR9 6SX, St. Columb Major, Cornwall · Great Britain

☎ +44-12-08816062 · 📠 +44-12-08816708

info@wiska.co.uk · www.wiska.co.uk