

Solar light

XSolar SOL-O HN

Anthracite

EAN 4007841 065935

Article number 065935



365 TAGE
LIGHT

Light 365 days of
the year

3000 K

3000K warm-white



Twilight switch



IP44



2 lux



soft light start

3 years

manufacturer's
warranty
steinel.de/
garantie3y



electricity
independent



energy saving



CE

Function description

Light for free. The solar light illuminates your house number without cables or costs – with nothing but energy from the sun. At dusk, light come ON automatically. In this version too, the patented intelligent microprocessor control system and the powerful lithium-iron-phosphate rechargeable batteries provide ensure reliable illumination. 365 days of the year. With night-light function, soft light start and evening light (4 h). Including adhesive house numbers.

Technical specifications

Dimensions (L x W x H)	91 x 242 x 183 mm
With lamp	Yes, STEINEL LED system
With motion detector	No
Manufacturer's Warranty	3 years
Settings via	Potentiometers
Version	Anthracite
PU1, EAN	4007841065935
Application, place	Outdoors
Application, room	outdoors, front door, courtyard & driveway
Colour	Anthracite
includes sheet of self-adhesive numbers	Yes
Installation site	wall
Impact resistance	IK03
IP-rating	IP44
Protection class	III

Mounting height max.	2,50 m
Photo-cell controller	Yes
Measured luminous flux (360°)	7 lm
Colour temperature	3000 K
Colour variation LED	SDCM5
Colour Rendering Index	80-89
Lamp	LED cannot be replaced
LED life expectancy (max. °C)	50000 h
Drop in luminous flux in accordance with LM80	L70B10
LED cooling system	Passive Thermo Control
Soft light start	Yes
Functions	Light sensor
Twilight setting	2 lx
Basic light level function	Yes
Basic light level function time	all night

<https://www.steinel.de>

Subject to technical modifications

05.2023 Page 1 from 2

Solar light

XSolar SOL-O HN

Anthracite

EAN 4007841 065935

Article number 065935



Technical specifications

Ambient temperature	-20 – 40 °C
Housing material	Aluminium
Cover material	Plastic, structured
Power supply, detail	Solar supply, no mains power required, Lithium-iron-phosphate rechargeable battery 2000 mAh

Output	0,07 W
Akku-Ladung	ab 0°
Akku-Funktion	ab - 20

Dimension Drawing

