Item no.: 1030540



# Presence and motion detectors Indoor detectors

### Description

- Passive infra-red motion detector for ceiling installation in false ceilings
- Circular detection area 360°, up to Ø 8 m (50 m²) at mounting height 3 m
- 1 channel light (Relay 230 V)
- Automatic motion and brightness-dependent control for lighting
- Daylight sensor mode for brightness-dependent control of the lighting, switchable via app
- Mixed light measurement
- Operation as fully automatic device
- Brightness switching value configurable, teach-in function
- Pulse function for staircase light time switch
- Time delay configurable
- Detection sensitivity configurable
- Test mode for checking function and detection area
- Ready for immediate use due to factory presetting (Brightness switching value 300 lux, Time delay 10 min.)
- One of these optional remote controls is required for changing the values and attitudes:
- Management remote control SendoPro
- Installation remote control theSenda P
- Optional user remote control: theSenda S





Item no.: 1030540




### Technical data

	theMova S360-100 FLAT DE WH	
Operating voltage	230 V AC	
Frequency	50 Hz	
Installation height	2 – 4 m	
Installation type	Ceiling installation	
Colour	White	
Switching output	Light	
Power consumption	~0.5 W	
Light measurement	Mixed light measurement	
Setting range brightness	30 – 3000 lx	
Light switch-off delay	10 s - 60 min	
Type of contact light	Relay 230 V/10 A µ-contact	
Lamps	Incandescent/halogen lamps, fluorescent lamps, Energy saving lamps, LEDs	

	theMova S360-100 FLAT DE WH	
Incandescent/halogen lamp load	2300 W	
Compact and flourescent lamps	1150 VA (cos φ = 0,5)	
Inrush current	max. 400 A / 200 μs	
LED lamp < 2 W	25 W	
LED lamp 2-8 W	250 W	
LED lamp > 8 W	250 W	
Type of connection	Spring terminals	
Detection range	50 m² (ø 8 m   360°)	
Detection angle	360°	
Ambient temperature	-15°C 50°C	
Impact resistance	IK04	
Type of protection	IP 54 (when fitted)	
Ambient temperature Impact resistance	-15°C 50°C IK04	

## Connection example




## Detection range for planning applications at a temperature of 21 °C


Mounting height (A)	Head on to (R)	Diagonally (t)
2 m	5 m <sup>2</sup>   2.5 m	38 m²   7 m
2.5 m	7 m²   3 m	38 m²   7 m
3 m	13 m²   4 m	50 m²   8 m
3.5 m	13 m²   4 m	50 m²   8 m
4 m	13 m²   4 m	64 m²   9 m

Item no.: 1030540




## Detection range for planning applications at a temperature of 21 °C





### Scale drawings



### Accessories

theSenda P Item no.: 9070910



theSenda S Item no.: 9070911



theSenda B Item no.: 9070985



Cover FLAT 85 GR Item no.: 9070597



Subject to technical changes and misprints additional information at: www.theben.de/product/1030540

Item no.: 1030540



### Accessories

Cover FLAT 85 BK Item no.: 9070853

